

# Battery Shaker KM 2 Akku



## Description

The Battery Shaker KM 2 Akku with orbital motion can be used for various tasks thanks to its off-grid battery with a run time of min. 40 hours. The shaking platform of 200 x 295 mm can be loaded with max. 2 kg. The stroke of the laboratory shaker KM 2 Akku is 20 mm and the shaking speed is between 5 and 220 rpm.

### Basic Equipment

Basic device incl. basic platform and rubber mat, with battery charger / power unit

### Loading Capacity

Erlenmeyer flasks 10 ml 20 pieces

Erlenmeyer flasks 50 ml 12 pieces

You will find further loading possibilities [here](#)

## Details

<b>Motion:</b>	orbital
<b>Shaking platform:</b>	200 x 295 mm
<b>Max. load:</b>	2 kg
<b>Shaking speed:</b>	5 - 220 rpm, in steps of 5
<b>Stroke:</b>	20 mm
<b>Battery charging time:</b>	approx. 10 h
<b>Runtime Battery:</b>	min. 40 h
<b>Runtime with mains cable:</b>	0 - 99 h 59 min / continuous
<b>Order No.:</b>	6135 000
<b>Accessory:</b>	Universal tray KM Mini Universal tray KM Clamping strip KM

## Technical specifications

<b>Electrical supply battery charger:</b>	100 - 240 V, 50 / 60 Hz
<b>Internal electrical supply:</b>	1 battery 12 V / 7 Ah
<b>Enclosure protection:</b>	IP 21
<b>Heat emission:</b>	approx. 0,5 - 2 W
<b>Ambient temperature:</b>	4°C to 45°C
<b>Relative humidity:</b>	~ 95 % (non-condensing)
<b>Dimensions (w x d x h):</b>	250 x 415 x 145 mm
<b>Weight:</b>	10,5 kg