

Multi-Flask Shaker VKS 75 A control



Description

Big heavy-duty shaker VKS 75 A control with touch display and programmable control has an orbital shaking motion, a speed range of 30 - 200 rpm and a stroke of 26 mm. The VKS 75 A control is ideally suited for high loads up to 75 kg. **(floor installation only!)**

Basic Equipment

Basic device **without shaking plate, without rack system**

With touch display and programmable control

Loading Capacity

Erlenmeyer flasks 500 ml 34 pieces

Erlenmeyer flasks 2000 ml 12 pieces

Separating funnels 1000 ml 6 pieces

You will find further loading possibilities [here](#)

[Loading details](#) against shaking speed.

Options

[USB 2.0 interface](#)

[RS 232 interface](#)

[Control interface](#)

[Safety Package](#)

[Defined stop](#)

Details

Motion:	orbital
Shaking platform:	760 x 600 mm
Max. load:	75 kg
Shaking Speed:	30 - 200 rpm, in steps of 5
Stroke:	26 mm
Runtime:	programmable / continuous
Order no.:	6111 000
Accessory:	Shaking plate VKS (1-storey) Rack System Combifix VKS A Rack System Combifix VKS B Rack System Combifix VKS C Universal tray VKS 1-storey Rack System VKS (2-storey) Rack System VKS "Giant" (3-storey)

Technical specifications

Electrical supply:	100 - 240 V, 50 / 60 Hz please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	max. 15 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	1050 x 835 x 250 mm
Weight:	110 kg