

Multi-Flask Shaker VKS 75 B control with emergency stop



Description

The big heavy-duty shaker VKS 75 B control with touch display and programmable control has a horizontal shaking motion, a speed range of 30 - 200 rpm and a stroke of 50 mm. The VKS 75 B control is ideally suited for high loads up to 75 kg. **(floor installation only!)**

Basic Equipment

Basic device **without shaking plate, without rack system**

With emergency stop, touch display and programmable control

Loading Capacity

Erlenmeyer flasks 500 ml 34 pieces

Erlenmeyer flasks 2000 ml 12 pieces

Separating funnels 1000 ml 6 pieces

You will find further loading possibilities [here](#)

[Loading details](#) against shaking speed

Options:

[Stroke 36 mm](#)

[Stroke 60 mm](#)

[Stroke 80 mm](#)

Details

Motion:	reciprocating (horizontal)
Shaking platform:	760 x 600 mm
Max. load:	75 kg
Shaking speed:	30 - 200 rpm, in steps of 5
Stroke:	50 mm (option: 36, 60 or 80 mm)
Timer:	programmable / continuous
Order no.:	6112 S02
Accessory:	Shaking plate VKS (1-storey) Rack System Combifix VKS A Rack System Combifix VKS B Rack System Combifix VKS C Universal tray VKS 1-storey Rack System VKS (2-storey) Rack System VKS "Giant" (3-storey)

Technical specifications

Electrical supply:	100 - 240 V, 50 / 60 Hz please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	max. 15 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	1050 x 835 x 250 mm
Weight:	110 kg